

# Praxair Material Safety Data Sheet

## 1. Chemical Product and Company Identification

<b>Product Name:</b> Deuterium, compressed (MSDS No. P-4585-E)	<b>Trade Names:</b> Deuterium
<b>Chemical Name:</b> Deuterium	<b>Synonyms:</b> Heavy hydrogen
<b>Chemical Family:</b> Permanent gas	<b>Product Grades:</b> 2.7
<b>Telephone:</b>	<b>Company Name:</b> Praxair, Inc.
<b>Emergencies:</b> 1-800-645-4633*	39 Old Ridgebury Road
<b>CHEMTREC:</b> 1-800-424-9300*	Danbury, CT 06810-5113
<b>Routine:</b> 1-800-PRAXAIR	

\*Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).

## 2. Hazards Identification

### EMERGENCY OVERVIEW

**DANGER! Flammable high-pressure gas.**

**Can form explosive mixtures with air.**

**May ignite if valve is opened to air.**

**Burns with invisible flame.**

**May cause dizziness and drowsiness.**

**Self-contained breathing apparatus may be required by rescue workers.**

**Under ambient conditions, this is a colorless, odorless gas.**

**OSHA REGULATORY STATUS:** This material is considered hazardous by the OSHA Hazard Communications Standard (29 CFR 1910.1200).

### POTENTIAL HEALTH EFFECTS:

#### Effects of a Single (Acute) Overexposure

**Inhalation.** Asphyxiant. Effects are due to lack of oxygen. Moderate concentrations may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Lack of oxygen can kill.

**Skin Contact.** No harm expected.

**Swallowing.** An unlikely route of exposure; this product is a gas at normal temperature and pressure.

**Eye Contact.** No harm expected.

**Effects of Repeated (Chronic) Overexposure.** No harm expected.

**Other Effects of Overexposure.** Deuterium is an asphyxiant. Lack of oxygen can kill.

**Medical Conditions Aggravated by Overexposure.** The toxicology and the physical and chemical properties of deuterium suggest that overexposure is unlikely to aggravate existing medical conditions.

**CARCINOGENICITY:** Deuterium is not listed by NTP, OSHA, or IARC.

**POTENTIAL ENVIRONMENTAL EFFECTS:** None known. For further information, see section 12, Ecological Information.

### 3. Composition/Information on Ingredients

See section 16 for important information about mixtures.

COMPONENT	CAS NUMBER	CONCENTRATION
Deuterium	7782-39-0	>99%*

\*The symbol > means "greater than."

### 4. First Aid Measures

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

**SKIN CONTACT:** Wash with soap and water. If irritation persists, seek medical attention.

**SWALLOWING:** An unlikely route of exposure. This product is a gas at normal temperature and pressure.

**EYE CONTACT:** Flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Get medical attention if discomfort persists.

**NOTES TO PHYSICIAN:** *There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.*

### 5. Fire Fighting Measures

**FLAMMABLE PROPERTIES:** Flammable gas.

**SUITABLE EXTINGUISHING MEDIA:** CO<sub>2</sub>, dry chemical, water spray, or fog

**PRODUCTS OF COMBUSTION:** None known.

**PROTECTION OF FIREFIGHTERS: DANGER! Flammable high-pressure gas.** Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool; then move them away from fire area if without risk. Continue cooling water spray while moving cylinders. Do not extinguish flames emitted from cylinders; allow them to burn out. Self-contained breathing apparatus may be required by rescue workers. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

**Specific Physical and Chemical Hazards.** Flame is nearly invisible. Escaping gas may ignite spontaneously. Deuterium has a low ignition energy. Fireball forms if gas cloud ignites immediately after release.

Forms explosive mixtures with air and oxidizing agents. Heat of fire can build pressure in cylinder and cause it to rupture. Deuterium cylinders are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.) No part of a cylinder should be subjected to a temperature higher than 125°F (52°C). If venting or leaking deuterium catches fire, do not

extinguish flames. Flammable gas may spread from leak, creating an explosive re-ignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with approved explosion meter.

**Protective Equipment and Precautions for Firefighters.** Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear.

## 6. Accidental Release Measures

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**DANGER! Flammable high-pressure gas.**

**Personal Precautions.** Forms explosive mixtures with air. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Remove all sources of ignition if without risk. Reduce gas with fog or fine water spray. Shut off flow if without risk. Ventilate area or move cylinder to a well-ventilated area. Flammable gas may spread from leak. Before entering area, especially confined areas, check atmosphere with an appropriate device.

**Environmental Precautions.** Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

## 7. Handling and Storage

**PRECAUTIONS TO BE TAKEN IN HANDLING:** Use only spark-proof tools and explosion-proof equipment. Keep away from heat, sparks, and open flame. ***Gas can cause rapid suffocation due to oxygen deficiency.*** Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Deuterium is among the lightest known gases. It may leak out of systems that are air-tight for other gases and may collect in poorly ventilated upper reaches of buildings. All piped deuterium systems and associated equipment must be grounded. Electrical equipment must be non-sparking or explosion-proof. Leak check system with soapy water; never use a flame. Do not crack or open disconnected deuterium cylinder valves; escaping gas may ignite spontaneously. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions in using deuterium, see section 16.

**PRECAUTIONS TO BE TAKEN IN STORAGE:** Store and use with adequate ventilation. Separate deuterium cylinders from oxygen, chlorine, and other oxidizers by at least 20 ft (6.1 m), or use a barricade of noncombustible material. This barricade should be at least 5 ft (1.53 m) high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

**RECOMMENDED PUBLICATIONS:** For further information on storage, handling, and use, see Praxair publication P-14-153, *Guidelines for Handling Gas Cylinders and Containers*. Obtain from your local supplier.

## 8. Exposure Controls/Personal Protection

COMPONENT	OSHA PEL	ACGIH TLV-TWA (2008)
Deuterium	Not Established.	Not Established.

IDLH = Not available.

### ENGINEERING CONTROLS:

**Local Exhaust.** An explosion-proof local exhaust system is acceptable. See SPECIAL.

**Mechanical (General).** Inadequate; see SPECIAL.

**Special.** Use only in a closed system.

**Other.** See SPECIAL.

### PERSONAL PROTECTIVE EQUIPMENT:

**Skin Protection.** Wear work gloves for cylinder handling. Metatarsal shoes for cylinder handling. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. Regardless of protective equipment, never touch live electrical parts.

**Eye/Face Protection.** Select in accordance with OSHA 29 CFR 1910.133.

**Respiratory Protection.** None required. However, air supplied respirators are required while working in oxygen deficient atmospheres such as confined spaces.

## 9. Physical and Chemical Properties

<b>APPEARANCE:</b>	Colorless gas
<b>ODOR:</b>	Odorless
<b>ODOR THRESHOLD:</b>	Not available.
<b>PHYSICAL STATE:</b>	Colorless gas at normal temperature and pressure
<b>pH:</b>	Not applicable.
<b>MELTING POINT</b> at 1 atm:	-425.96°F (-254.42°C)
<b>BOILING POINT</b> at 1 atm:	-417.1°F (-249.5°C)
<b>FLASH POINT</b> (test method):	Not available.
<b>EVAPORATION RATE</b> (Butyl Acetate = 1):	82 (estimated)
<b>FLAMMABILITY:</b>	Flammable
<b>FLAMMABLE LIMITS IN AIR</b> , % by volume:	<b>LOWER:</b> 5% <b>UPPER:</b> 75%
<b>VAPOR PRESSURE</b> at 68°F (20°C):	Not Available.
<b>VAPOR DENSITY</b> at 70°F (21.1°C) and 1 atm:	0.0104 lb/ft <sup>3</sup> (0.167 kg/m <sup>3</sup> )
<b>SPECIFIC GRAVITY</b> (H <sub>2</sub> O = 1) at 19.4°F (-7°C):	Not Available.
<b>SPECIFIC GRAVITY</b> (Air = 1) at 70°F (21.1°C) and 1 atm:	0.139
<b>SOLUBILITY IN WATER</b> , wt/wt at 77°F (25°C) and 1 atm:	3.16 ppm

---

**PARTITION COEFFICIENT: n-octanol/water:** Not available.

---

**AUTOIGNITION TEMPERATURE:** 752°F (400°C)

---

**DECOMPOSITION TEMPERATURE:** Not available.

---

**PERCENT VOLATILES BY VOLUME:** 100

---

**MOLECULAR WEIGHT:** 4.032

---

**MOLECULAR FORMULA:** D<sub>2</sub>

### 10. Stability and Reactivity

**CHEMICAL STABILITY:**  Unstable  Stable**CONDITIONS TO AVOID:** Air**INCOMPATIBLE MATERIALS:** Oxidizing agents, halogens, alkali metals, alkaline earth metals, ductile metals, cold-worked ferritic steels**HAZARDOUS DECOMPOSITION PRODUCTS:** None**POSSIBILITY OF HAZARDOUS REACTIONS:**  May Occur  Will Not Occur

May ignite if exposed to air.

### 11. Toxicological Information

**ACUTE DOSE EFFECTS:** None known.**STUDY RESULTS:** None known.

### 12. Ecological Information

**ECOTOXICITY:** No known effects.**OTHER ADVERSE EFFECTS:** Deuterium does not contain any Class I or Class II ozone-depleting chemicals.

### 13. Disposal Considerations

**WASTE DISPOSAL METHOD:** Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

### 14. Transport Information

**DOT/IMO SHIPPING NAME:** Deuterium, compressed

HAZARD CLASS:	PACKING GROUP/Zone:	IDENTIFICATION NUMBER:	PRODUCT RQ:
2.1	NA/NA*	UN1957	None

**SHIPPING LABEL(s):** FLAMMABLE GAS**PLACARD (when required):** FLAMMABLE GAS

\*NA= Not applicable.

**SPECIAL SHIPPING INFORMATION:** Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

**MARINE POLLUTANTS:** Deuterium is not listed as a marine pollutant by DOT.

## 15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

### U.S. FEDERAL REGULATIONS:

EPA (ENVIRONMENTAL PROTECTION AGENCY)

CERCLA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):

**Reportable Quantity (RQ):** None

SARA: SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:

**SECTIONS 302/304:** Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):

**TPQ:** None

**EHS RQ (40 CFR 355):** None

**SECTIONS 311/312:** Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:

**IMMEDIATE:** No

**PRESSURE:** Yes

**DELAYED:** No

**REACTIVITY:** No

**FIRE:** Yes

**SECTION 313:** Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

Deuterium is not subject to reporting under Section 313.

**40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION:** Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

Deuterium is not listed as a regulated substance.

**TSCA: TOXIC SUBSTANCES CONTROL ACT:** Deuterium is listed on the TSCA inventory.

**OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:**

**29 CFR 1910.119: PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

Deuterium is not listed in Appendix A as a highly hazardous chemical. However, any process that involves a flammable gas on site in one location in quantities of 10,000 lb (4536 kg) or greater is covered under this regulation unless the gas is used as a fuel.

**STATE REGULATIONS:**

**CALIFORNIA:** Deuterium is not listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).

**PENNSYLVANIA:** Deuterium is subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

**16. Other Information**

Be sure to read and understand all labels and instructions supplied with all containers of this product.

**OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:** *Flammable high-pressure gas. Use only in a closed system.* Use piping and equipment adequately designed to withstand pressures and temperatures to be encountered. Use a backflow prevention device. Use only in a closed system. Store and use with adequate ventilation. Close cylinder valve after each use; keep closed even when empty. *Never work on a pressurized system.* If there is a leak, close the cylinder valve. Blow the system down in a safe and environmentally sound manner in compliance with all federal, state, and local laws; then repair the leak. *Never place a compressed gas cylinder where it may become part of an electrical circuit.*

**Mixtures.** When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

**HAZARD RATING SYSTEMS:****NFPA RATINGS:**

HEALTH = 0  
FLAMMABILITY = 4  
INSTABILITY = 0  
SPECIAL = None

**HMIS RATINGS:**

HEALTH = 0  
FLAMMABILITY = 4  
PHYSICAL HAZARD = 3

**STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:**

**THREADED:** CGA-350, CGA-180, 110 (lecture bottle)  
**PIN-INDEXED YOKE:** Not applicable.  
**ULTRA-HIGH-INTEGRITY CONNECTION:** Not applicable.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlet V-1 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information can be found in the following materials published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5<sup>th</sup> Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, <http://www.cganet.com/Publication.asp>.

AV-1 *Safe Handling and Storage of Compressed Gases*  
P-1 *Safe Handling of Compressed Gases in Containers*  
SB-2 *Oxygen-Deficient Atmospheres*  
V-1 *Compressed Gas Cylinder Valve Inlet and Outlet Connections*  
— *Handbook of Compressed Gases, Fourth Edition*

Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

---

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

---

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current MSDSs for these products, contact your Praxair sales representative or local distributor or supplier, or download from [www.praxair.com](http://www.praxair.com). If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

*Praxair* and the *Flowing Airstream* design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.



Praxair, Inc.  
39 Old Ridgebury Road  
Danbury, CT 06810-5113