



**Eye Contact.** Exposure to the eye causes immediate pain and irritation with excess tear production and closure of the eyelids. The severity of the injury depends on the concentration and duration of contact and may range from slight excess redness and irritation of the conjunctiva to total corneal opacification and blindness.

**Effects of Repeated (Chronic) Overexposure.** Prolonged or repeated exposure to vapor may discolor or erode the teeth, cause the nose and gums to bleed, and ulcerate the nasal mucosa.

**Other Effects of Overexposure.** None known.

**Medical Conditions Aggravated by Overexposure.** Breathing of vapor or mist may aggravate asthma and inflammatory or fibrotic pulmonary disease. Skin contact may aggravate an existing dermatitis.

**CARCINOGENICITY:** Hydrogen chloride is not listed by NTP and OSHA. IARC lists hydrogen chloride under *Group 3, Not classifiable as to its carcinogenicity to humans.*

**POTENTIAL ENVIRONMENTAL EFFECTS:** None known. For further information, see section 12, Ecological Information.

### 3. Composition/Information on Ingredients

See section 16 for important information about mixtures.

COMPONENT	CAS NUMBER	CONCENTRATION
Hydrogen Chloride	7647-01-0	>99%*
<i>*The symbol &gt; means "greater than."</i>		

### 4. First Aid Measures

**INHALATION:** Immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Keep victim warm. Seek medical attention promptly.

**SKIN CONTACT:** Immediately flush skin with plenty of water while removing contaminated clothing and shoes. Discard clothing and shoes.

**SWALLOWING:** Rinse mouth with water. Give two glasses of water. Do not induce vomiting. Call a physician.

**EYE CONTACT:** Immediately flush eyes thoroughly with warm water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. See a physician, preferably an ophthalmologist, immediately.

**NOTES TO PHYSICIAN:** *Keep victims of overexposure under medical observation for 24-48 hours. The hazards of this material are mainly due to its severely irritant and corrosive properties on skin and mucosal surfaces. There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.*

Contact the Poison Control Center in your area for additional information on patient management and follow-up.

## 5. Fire Fighting Measures

**FLAMMABLE PROPERTIES:** Hydrogen chloride cannot catch fire.

**SUITABLE EXTINGUISHING MEDIA:** Use media appropriate for surrounding fire, but note incompatibilities in section 10.

**PRODUCTS OF COMBUSTION:** Not applicable. Decomposition due to heating may produce hydrogen and chlorine or chlorides. (See section 10.)

**PROTECTION OF FIREFIGHTERS: Toxic, corrosive, high-pressure liquid and gas (see section 3).** Immediately evacuate all personnel from danger area. Do not approach area without self-contained breathing apparatus, protective clothing, and eye protection. Immediately cool cylinders with water spray from maximum distance; then move them away from fire if without risk. If cylinders are leaking, reduce toxic vapors with water spray or fog. Shut off leak if without risk. Reverse flow into cylinders may cause rupture. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

**Specific Physical and Chemical Hazards.** Heat of fire can build pressure in cylinder and cause it to rupture. No part of cylinder should be subjected to a temperature higher than 125°F (52°C). Hydrogen chloride cylinders are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.) Liquid and vapors are extremely irritating and may burn skin and eyes on contact. Contact with most metals in the presence of moisture produces flammable hydrogen.

**Protective Equipment and Precautions for Firefighters.** Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

**DANGER! Toxic, corrosive, high-pressure liquid and gas.**

**Personal Precautions.** Immediately evacuate all personnel from danger area. Do not approach area without self-contained breathing apparatus and protective clothing. Reduce vapors with fog or fine water spray. Shut off leak if without risk. Ventilate area of leak or move cylinder to a well-ventilated area. Prevent runoff from contaminating the surrounding environment. Toxic, corrosive vapors may spread from spill. Before entering area, especially a confined area, check atmosphere with an appropriate device. Reverse flow into cylinders may cause rupture.

**Environmental Precautions.** Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

## 7. Handling and Storage

**PRECAUTIONS TO BE TAKEN IN HANDLING:** Do not breathe gas. Do not get vapor or liquid in eyes, on skin, or on clothing. Have safety showers and eyewash fountains immediately available. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove

over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions in using hydrogen chloride, see section 16.

**PRECAUTIONS TO BE TAKEN IN STORAGE:** Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

**RECOMMENDED PUBLICATIONS:** For further information on storage, handling, and use, see Praxair publication P-14-153, *Guidelines for Handling Gas Cylinders and Containers*. Obtain from your local supplier.

## 8. Exposure Controls/Personal Protection

COMPONENT	OSHA PEL	ACGIH TLV-TWA (2008)
Hydrogen Chloride	5 ppm (c)*	2 ppm (c)*

\*(c) – ceiling. Ceiling values are not Time-Weighted-Average (TWA).

TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

IDLH = 50 ppm

### ENGINEERING CONTROLS:

**Local Exhaust.** Use a corrosion-resistant system with sufficient air flow to keep the hydrogen chloride concentration below the applicable exposure limits in the worker's breathing zone.

**Mechanical (General).** Not recommended as a primary ventilation system to control worker's exposure.

**Special.** A corrosion-resistant, canopy type, forced-draft fume hood may be preferred for some applications.

**Other.** None

### PERSONAL PROTECTIVE EQUIPMENT:

**Skin Protection.** Wear work gloves for cylinder handling. Neoprene where contact with product could occur.

**Eye/Face Protection.** Wear safety glasses when handling cylinders; vapor-proof goggles where contact with product could occur. Select per OSHA 29 CFR 1910.133. Metatarsal shoes for cylinder handling and protective clothing where needed. Select per OSHA 29 CFR 1910.132 and 1910.133. Regardless of protective equipment, never touch live electrical parts.

**Respiratory Protection.** A respiratory protection program that meet OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable) requirements must be followed whenever workplace conditions warrant respirator use. Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus.

### 9. Physical and Chemical Properties

<b>APPEARANCE:</b>	Colorless gas. Produces white fumes in moist air.
<b>ODOR:</b>	Pungent, suffocating
<b>ODOR THRESHOLD:</b>	Not available.
<b>PHYSICAL STATE:</b>	Gas at normal temperature and pressure
<b>pH:</b>	Not applicable.
<b>MELTING POINT</b> at 1 atm:	-173.5°F (-114.2°C)
<b>BOILING POINT</b> at 1 atm:	-121°F (-85°C)
<b>FLASH POINT</b> (test method):	Not applicable.
<b>EVAPORATION RATE</b> (Butyl Acetate = 1):	High
<b>FLAMMABILITY:</b>	Nonflammable
<b>FLAMMABLE LIMITS IN AIR</b> , % by volume:	<b>LOWER:</b> Not applicable. <b>UPPER:</b> Not applicable.
<b>VAPOR PRESSURE</b> at 69°F (20°C):	627.7 psia (4327 kPa, abs)
<b>VAPOR DENSITY</b> at 70°F (21.1°C) and 1 atm:	0.0943 lb/ft <sup>3</sup> (1.510 kg/m <sup>3</sup> )
<b>SPECIFIC GRAVITY</b> (H <sub>2</sub> O = 1) at -121°F (-85°C) and 1 atm:	1.187
<b>SPECIFIC GRAVITY</b> (Air = 1) at 68°F (20°C) and 1 atm:	1.26
<b>SOLUBILITY IN WATER</b> , at 32°F (0°C) and 1 atm, wt/wt solution:	0.823
<b>PARTITION COEFFICIENT: n-octanol/water:</b>	Not available.
<b>AUTOIGNITION TEMPERATURE:</b>	Not applicable.
<b>DECOMPOSITION TEMPERATURE:</b>	Not available.
<b>PERCENT VOLATILES BY VOLUME:</b>	100
<b>MOLECULAR WEIGHT:</b>	36.46
<b>MOLECULAR FORMULA:</b>	HCl <sub>2</sub>

### 10. Stability and Reactivity

**CHEMICAL STABILITY:**     Unstable     Stable

**CONDITIONS TO AVOID:** None known.

**INCOMPATIBLE MATERIALS:** Bases, unsaturated organics, most common metals and their alloys, fluorine, metal carbides, metal acetylides, potassium permanganate, sulfuric acid.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Decomposition may produce hydrogen and chlorine or chlorides.

**POSSIBILITY OF HAZARDOUS REACTIONS:**     May Occur     Will Not Occur

Decomposition may produce hydrogen and chlorine or chlorides.

### 11. Toxicological Information

**ACUTE DOSE EFFECTS:** LC<sub>50</sub>, 1 hr, rat = 3120 ppm

**STUDY RESULTS:** None known.

## 12. Ecological Information

**ECOTOXICITY:** No known effects.

**OTHER ADVERSE EFFECTS:** Hydrogen chloride does not contain any Class I or Class II ozone-depleting chemicals.

## 13. Disposal Considerations

**WASTE DISPOSAL METHOD:** Keep waste away from surrounding environment. Keep personnel away. Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

## 14. Transport Information

**DOT/IMO SHIPPING NAME:** Hydrogen chloride, anhydrous

HAZARD CLASS:	PACKING GROUP/Zone:	IDENTIFICATION NUMBER:	PRODUCT RQ:
2.3	NA/C	UN1050	5000 lb (2270 kg)

**SHIPPING LABEL(s):** POISON GAS, CORROSIVE\*\*

**PLACARD (when required):** POISON GAS, CORROSIVE\*\*

\*NA=Not applicable.

\*\*The words in the POISON GAS diamond are INHALATION HAZARD.

**SPECIAL SHIPPING INFORMATION:** Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

**Additional Marking Requirement:** INHALATION HAZARD

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

**MARINE POLLUTANTS:** Hydrogen chloride is not listed as a marine pollutant by DOT.

## 15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

### U.S. FEDERAL REGULATIONS:

EPA (ENVIRONMENTAL PROTECTION AGENCY)

CERCLA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):

**Reportable Quantity (RQ):** 5000 lb (2268 kg)

SARA: SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:

**SECTIONS 302/304:** Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):

**TPQ:** 500 lb (227 kg)

**EHS RQ (40 CFR 355):** 5000 lb (2268 kg)

**SECTIONS 311/312:** Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:

**IMMEDIATE:** Yes

**DELAYED:** Yes

**PRESSURE:** Yes

**REACTIVITY:** No

**FIRE:** No

**SECTION 313:** Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

Hydrogen chloride is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40CFR Part 372.

**40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION:** Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

Hydrogen chloride is listed as a regulated substance in quantities of 5000 lb (2268 kg) or greater.

**TSCA: TOXIC SUBSTANCES CONTROL ACT:** Hydrogen chloride is listed on the TSCA inventory.

**OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:**

29 CFR 1910.119: **PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

Hydrogen chloride is listed in Appendix A as a highly hazardous chemical in quantities of 5,000 lb (2268 kg) or greater.

#### **STATE REGULATIONS:**

**CALIFORNIA:** Hydrogen chloride is not listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).

**PENNSYLVANIA:** Hydrogen chloride is subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

### **16. Other Information**

Be sure to read and understand all labels and instructions supplied with all containers of this product.

**OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:** *Toxic, corrosive, high-pressure liquid and gas.* Use piping and equipment adequately designed to withstand pressures to be encountered. *Store and use with adequate ventilation at all times.* Use only in a sealed, pressure-tight system designed to prevent escape of product to the air. The system must be constructed of corrosion-resistant materials. Close cylinder valve after each use; keep closed even when empty. *Prevent reverse flow.* Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. *Never work on a pressurized system.* If there is a leak, close the cylinder valve. Blow the system down in a safe and environmentally sound manner in compliance with all federal, state, and local laws; then repair the leak. *Follow safe practices when returning cylinder to supplier.* Be sure valve is closed; then tightly install valve outlet cap or plug. *Never place a compressed gas cylinder where it may become part of an electrical circuit.*

**NOTE:** Prior to using any plastics, confirm their compatibility with hydrogen chloride.

**Mixtures.** When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

**RECOMMENDED EQUIPMENT:** In semiconductor process gas and other suitable applications, Praxair recommends the use of engineering controls such as gas cabinet enclosures, automatic gas panels (used to purge systems on cylinder changeout), excess-flow valves throughout the gas distribution system, double containment for the distribution system, and continuous gas monitors.

**HAZARD RATING SYSTEMS:**

**NFPA RATINGS:**

HEALTH = 3  
 FLAMMABILITY = 0  
 INSTABILITY = 1  
 SPECIAL = None

**HMIS RATINGS:**

HEALTH = 3  
 FLAMMABILITY = 0  
 PHYSICAL HAZARD = 3

**STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:**

**THREADED:** CGA-330 connection is standard.  
**PIN-INDEXED YOKE:** Not applicable.  
**ULTRA-HIGH-INTEGRITY CONNECTION:** CGA-634

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlet V-1 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information can be found in the following materials published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5<sup>th</sup> Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, <http://www.cganet.com/Publication.asp>.

- AV-1 *Safe Handling and Storage of Compressed Gases*
- P-1 *Safe Handling of Compressed Gases in Containers*
- V-1 *Compressed Gas Cylinder Valve Inlet and Outlet Connections*
- *Handbook of Compressed Gases, Fourth Edition*



Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

---

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

---

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current MSDSs for these products, contact your Praxair sales representative or local distributor or supplier, or download from [www.praxair.com](http://www.praxair.com). If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

*Praxair* and the *Flowing Airstream* design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.



Praxair, Inc.  
39 Old Ridgebury Road  
Danbury, CT 06810-5113