

# Praxair Material Safety Data Sheet

## 1. Chemical Product and Company Identification

<b>Product Name:</b> Natural gas, compressed (MSDS No. P-4627-E)	<b>Trade Names:</b> Natural Gas
<b>Chemical Name:</b> Mixture of methane, ethane, propane, and butane	<b>Synonyms:</b> Not applicable.
<b>Chemical Family:</b> Alkane	<b>Product Grades:</b> None assigned.
<b>Telephone:</b>	<b>Company Name:</b> Praxair, Inc.
<b>Emergencies:</b> 1-800-645-4633*	39 Old Ridgebury Road
<b>CHEMTREC:</b> 1-800-424-9300*	Danbury, CT 06810-5113
<b>Routine:</b> 1-800-PRAXAIR	

\*Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).

## 2. Hazards Identification

### EMERGENCY OVERVIEW

**DANGER! Flammable high-pressure gas.**  
**Can form explosive mixtures with air.**  
**May cause dizziness and drowsiness.**  
**Self-contained breathing apparatus may be required by rescue workers.**  
**Under ambient conditions, this colorless gas has a faintly, disagreeable odor.**

**OSHA REGULATORY STATUS:** The components of this mixture are considered hazardous by the OSHA Hazard Communications Standard (29 CFR 1910.1200).

### POTENTIAL HEALTH EFFECTS:

#### Effects of a Single (Acute) Overexposure

**Inhalation.** Asphyxiant. Effects are due to lack of oxygen. Moderate concentrations may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Lack of oxygen can kill.

**Skin Contact.** No harm expected.

**Swallowing.** An unlikely route of exposure. This product is a gas at normal temperature and pressure.

**Eye Contact.** No harm expected.

**Effects of Repeated (Chronic) Overexposure.** No harm expected.

**Other Effects of Overexposure.** Natural gas is an asphyxiant. Lack of oxygen can kill.

**Medical Conditions Aggravated by Overexposure.** The toxicology and the physical and chemical properties of natural gas suggest that overexposure is unlikely to aggravate existing medical conditions.

**CARCINOGENICITY:** None of the components of natural gas is listed by NTP, OSHA, or IARC.

**POTENTIAL ENVIRONMENTAL EFFECTS:** None known. For further information, see section 12, Ecological Information.

### 3. Composition/Information on Ingredients

This section covers materials of manufacture only. See sections 8, 10, 11, and 16 for information on by-products generated during use in welding and cutting.

See section 16 for important information about mixtures.

COMPONENT	CAS NUMBER*	CONCENTRATION
Methane	74-82-8	83-99%
Ethane	74-84-0	1-13%
Propane	74-98-6	0.1-3.0%
Butane	106-97-8	0.2-1.0%

\*The CAS number for natural gas is 8006-14-2.

### 4. First Aid Measures

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

**SKIN CONTACT:** Wash with soap and water.

**SWALLOWING:** An unlikely route of exposure. This product is a gas at normal temperature and pressure.

**EYE CONTACT:** Flush eyes with warm water. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. If discomfort persists, see a physician, preferably an ophthalmologist.

**NOTES TO PHYSICIAN:** *There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.*

### 5. Fire Fighting Measures

**FLAMMABLE PROPERTIES:** Flammable gas.

**SUITABLE EXTINGUISHING MEDIA:** CO<sub>2</sub>, dry chemicals, water spray, or fog.

**PRODUCTS OF COMBUSTION:** Carbon monoxide, carbon dioxide

**PROTECTION OF FIREFIGHTERS: DANGER! Flammable high-pressure gas.** Evacuate all personnel from danger area. Immediately spray cylinders with water from maximum distance until cool, taking care not to extinguish flames. Remove ignition sources if without risk. Remove all cylinders from area of fire if without risk, while continuing cooling water spray. Do not extinguish any flames emitted from cylinders. Stop flow of gas if without risk, or allow flames to burn out. Self-contained breathing apparatus may be required by rescue workers. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

**Specific Physical and Chemical Hazards.** Forms explosive mixtures with air and oxidizing agents. Heat of fire can build pressure in cylinder and cause it to rupture. No part of cylinder should be subjected to a temperature higher than 125°F (52°C). Natural gas cylinders are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.) If venting or leaking natural gas catches fire, do not extinguish flames. Flammable gas may

spread from leak, creating an explosive re-ignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with an appropriate device. Self-contained breathing apparatus may be required by rescue workers.

**Protective Equipment and Precautions for Firefighters.** Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear.

## 6. Accidental Release Measures

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**DANGER! Flammable liquid and gas under pressure.**

**Personal Precautions.** Forms explosive mixtures with air. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Remove all sources of ignition if without risk. Reduce vapors with fog or fine water spray. Shut off flow if without risk. Ventilate area or move cylinder to a well-ventilated area. Flammable vapors may spread from leak. Before entering area, especially confined areas, check atmosphere with an approved device

**Environmental Precautions.** Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

## 7. Handling and Storage

**PRECAUTIONS TO BE TAKEN IN HANDLING:** May form explosive mixtures with air. Use only spark-proof tools and explosion-proof equipment. Ground all equipment. Keep away from heat, sparks, and open flame. ***Gas can cause rapid suffocation due to oxygen deficiency.*** Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. All piped natural gas systems and associated equipment must be grounded. Electrical equipment must be non-sparking or explosion-proof. Leak check system with soapy water; never use a flame. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions in using natural gas, see section 16.

**PRECAUTIONS TO BE TAKEN IN STORAGE:** Store and use with adequate ventilation. Separate natural gas cylinders from oxygen, chlorine, and other oxidizers by at least 20 ft (6.1 m) or use a barricade of noncombustible material. This barricade should be at least 5 ft (1.53 m) high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

**RECOMMENDED PUBLICATIONS:** For further information on storage, handling, and use, see Praxair publication P-14-153, *Guidelines for Handling Gas Cylinders and Containers*. Obtain from your local supplier.

## 8. Exposure Controls/Personal Protection

**See section 16 for important information on by-products generated during use in welding and cutting.**

COMPONENT	OSHA PEL	ACGIH TLV-TWA (2008)
Methane	N.E.*	1000 ppm**
Ethane	N.E.*	1000 ppm**
Propane	1000 ppm	1000 ppm**
Butane	N.E.*	1000 ppm**

\*N.E.—Not Established.

\*\*As aliphatic hydrocarbon gases.

TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

IDLH = Not available.

### ENGINEERING CONTROLS:

**Local Exhaust.** An explosion-proof local exhaust system is acceptable. See SPECIAL.

**Mechanical (General).** Inadequate; see SPECIAL.

**Special.** Use only in a closed system.

**Other.** None

### PERSONAL PROTECTIVE EQUIPMENT:

**Skin Protection.** Wear work gloves for cylinder handling; welding gloves for welding and cutting. Metatarsal shoes for cylinder handling. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. For welding, wear hand, head, and body protection. (See ANSI Z49.1.) Worn as needed, these help prevent injury from radiation, sparks, and electrical shock. Minimum protection includes welder's gloves and a face shield. For added protection, consider arm protectors, aprons, hats, shoulder protection, and dark, substantial clothing. Regardless of protective equipment, never touch live electrical parts.

**Eye/Face Protection.** Select in accordance with OSHA 29 CFR 1910.133. For welding, wear goggles with filter lenses; select per ANSI Z49.1. Provide protective screens and goggles if necessary to protect others.

**Respiratory Protection.** A respiratory protection program that meet OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable) requirements must be followed whenever workplace conditions warrant respirator use. Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus.

### 9. Physical and Chemical Properties

<b>APPEARANCE:</b>	Colorless gas
<b>ODOR:</b>	Faintly disagreeable
<b>ODOR THRESHOLD:</b>	Not available.
<b>PHYSICAL STATE:</b>	Gas at normal temperature and pressure
<b>pH:</b>	Not applicable.
<b>MELTING POINT</b> at 1 atm:	Not available.
<b>BOILING POINT</b> at 1 atm:	-263.2°F to -126.4°F (-164°C to -88°C)
<b>FLASH POINT</b> (test method):	Not available.
<b>EVAPORATION RATE</b> (Butyl Acetate = 1):	Not available.
<b>FLAMMABILITY:</b>	Flammable
<b>FLAMMABLE LIMITS IN AIR</b> , % by volume:	<b>LOWER:</b> 3.8% <b>UPPER:</b> 17.0%
<b>VAPOR PRESSURE</b> at 68°F (20°C):	Not available.
<b>VAPOR DENSITY</b> at 60°F (15.6°C) and 1 atm:	0.0412 lb/ft <sup>3</sup> (0.66 kg/m <sup>3</sup> )
<b>SPECIFIC GRAVITY</b> (H <sub>2</sub> O = 1) at 19.4°F (-7°C):	Not available.
<b>SPECIFIC GRAVITY</b> (Air = 1) at 60°F (15.6°C) and 1 atm:	0.70
<b>SOLUBILITY IN WATER</b> , vol/vol at 100°F (37.8°C) and 1 atm:	Negligible
<b>PARTITION COEFFICIENT: n-octanol/water:</b>	Not available.
<b>AUTOIGNITION TEMPERATURE:</b>	900-1170°F (482-632°C)
<b>DECOMPOSITION TEMPERATURE:</b>	Not available.
<b>PERCENT VOLATILES BY VOLUME:</b>	100
<b>MOLECULAR WEIGHT:</b>	101.007
<b>MOLECULAR FORMULA:</b>	Mixture of CH <sub>4</sub> , C <sub>2</sub> H <sub>6</sub> , C <sub>3</sub> H <sub>8</sub> , & C <sub>4</sub> H <sub>10</sub>

### 10. Stability and Reactivity

**CHEMICAL STABILITY:**     Unstable     Stable

**CONDITIONS TO AVOID:** None known.

**INCOMPATIBLE MATERIALS:** Oxidizing agents, halogens, acids

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition and burning may produce CO/CO<sub>2</sub>.

**POSSIBILITY OF HAZARDOUS REACTIONS:**     May Occur     Will Not Occur

Thermal decomposition and burning may produce CO/CO<sub>2</sub>.

### 11. Toxicological Information

**ACUTE DOSE EFFECTS:** The welding process may generate hazardous fumes and gases. (See sections 3, 10, 15, and 16.)

**STUDY RESULTS:** In a study conducted in 1948, dogs breathed varying mixtures of hydrocarbons and oxygen for 10 minutes. Dogs exposed to butane, ethane, and propane, minor components of this mixture, showed varying degrees of myocardial sensitivity to injected epinephrine hydrochloride as determined by electrocardiogram (EKG) readings. No direct evidence is known of cardiac sensitization in humans induced by any of these components.

### 12. Ecological Information

**ECOTOXICITY:** No known effects.

**OTHER ADVERSE EFFECTS:** Natural gas does not contain any Class I or Class II ozone-depleting chemicals.

### 13. Disposal Considerations

**WASTE DISPOSAL METHOD:** Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

### 14. Transport Information

**DOT/IMO SHIPPING NAME:** Natural gas, compressed

HAZARD CLASS:	PACKING GROUP/Zone:	IDENTIFICATION NUMBER:	PRODUCT RQ:
2.1	NA/NA*	UN1971	None
<b>SHIPPING LABEL(s):</b>		FLAMMABLE GAS	
<b>PLACARD (when required):</b>		FLAMMABLE GAS	

\* NA=Not applicable.

**SPECIAL SHIPPING INFORMATION:** Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

**MARINE POLLUTANTS:** None of natural gas's components are listed as marine pollutants by DOT.

### 15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

#### U.S. FEDERAL REGULATIONS:

EPA (ENVIRONMENTAL PROTECTION AGENCY)

CERCLA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):

**Reportable Quantity (RQ):** None

**SARA: SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:**

**SECTIONS 302/304:** Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):

**TPQ:** None

**EHS RQ (40 CFR 355):** None

**SECTIONS 311/312:** Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:

**IMMEDIATE:** No

**PRESSURE:** Yes

**DELAYED:** No

**REACTIVITY:** No

**FIRE:** Yes

**SECTION 313:** Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

None of the components of natural gas requires reporting under Section 313.

**40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION:** Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

The components of natural gas are listed as regulated substances in quantities of 10,000 lb (4536 kg) or greater.

**TSCA: TOXIC SUBSTANCES CONTROL ACT:** The components of natural gas are listed on the TSCA inventory.

**OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:**

**29 CFR 1910.119: PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

None of the components of natural gas is listed in Appendix A as a highly hazardous chemical. However, any process that involves a flammable gas on site in one location in quantities of 10,000 lb (4536 kg) or greater is covered under this regulation unless the gas is used as a fuel.

**STATE REGULATIONS:**

**CALIFORNIA:** None of the components of natural gas are listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).

**WARNING:** Combustion of this gas produces carbon monoxide—a chemical known to the State of California to cause birth defects or other reproductive harm.

*(California Health and Safety Code §25249.5 et seq.)*

**PENNSYLVANIA:** Natural gas is subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

**16. Other Information**

Be sure to read and understand all labels and instructions supplied with all containers of this product.

**OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:** *Flammable high-pressure gas.* Use piping and equipment adequately designed to withstand pressures to

be encountered. Use only in a closed system. **Store and use away from oxygen and oxidizing agents.** Store and use with adequate ventilation. Close cylinder valve after each use; keep closed even when empty. **Never work on a pressurized system.** If there is a leak, blow the system down in an environmentally safe manner in compliance with all federal, state, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.** When using compressed gases in and around electric welding applications, never ground the cylinders. Grounding exposes the cylinders to damage by the electric welding arc.

**NOTE:** Prior to using any plastics, confirm their compatibility with the components of natural gas.

**SPECIAL PRECAUTIONS: Use in welding and cutting.** Read and understand the manufacturer's instructions and the precautionary label on the product. Ask your welding products supplier for a copy of Praxair's free safety booklet, P-2035, *Precautions and Safe Practices for Gas Welding, Cutting, and Heating*, and for other manufacturers' safety publications. For a detailed treatment, get ANSI Z49.1, *Safety in Welding, Cutting, and Allied Processes*, published by the American Welding Society (AWS), or see OSHA's Web site at <http://www.osha-slc.gov/SLTC/weldingcuttingbrazing/>. Order AWS documents from Global Engineering Documents, 15 Inverness Way East, Englewood, CO 80112-5710, <http://global.ihs.com/>.

**Arcs and sparks can ignite combustible materials.** Prevent fires. For more information, get NFPA 51B, *Standard for Fire Prevention During Welding, Cutting, and Other Hotwork*, published by the National Fire Protection Association. **Do not strike an arc on the cylinder.** The defect produced by an arc burn could lead to cylinder rupture.

**Mixtures.** When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

#### HAZARD RATING SYSTEMS:

##### NFPA RATINGS:

HEALTH = 0  
 FLAMMABILITY = 4  
 INSTABILITY = 0  
 SPECIAL = None

##### HMIS RATINGS:

HEALTH = 0  
 FLAMMABILITY = 4  
 PHYSICAL HAZARD = 0

#### STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

**THREADED:** CGA-350 (Up to 3000 psig)  
**PIN-INDEXED YOKE:** Not applicable.  
**ULTRA-HIGH-INTEGRITY CONNECTION:** Not applicable.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlet V-1 listed below.



Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information can be found in the following materials published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5<sup>th</sup> Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, <http://www.cganet.com/Publication.asp>.

- AV-1 *Safe Handling and Storage of Compressed Gases*
- P-1 *Safe Handling of Compressed Gases in Containers*
- SB-2 *Oxygen-Deficient Atmospheres*
- SB-8 *Use of Oxy-Fuel Gas Welding and Cutting Apparatus*
- V-1 *Compressed Gas Cylinder Valve Inlet and Outlet Connections*
- V-7 *Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures*
- *Handbook of Compressed Gases, Fourth Edition*

Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

---

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

---

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current MSDSs for these products, contact your Praxair sales representative or local distributor or supplier, or download from [www.praxair.com](http://www.praxair.com). If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

*Praxair* and the *Flowing Airstream* design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.



Praxair, Inc.  
39 Old Ridgebury Road  
Danbury, CT 06810-5113