

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

| | |
|---|---|
| Product Name: Compressed gases, n.o.s. (argon, carbon dioxide, oxygen) or Compressed gases, n.o.s. (argon, carbon dioxide, nitrogen) (MSDS No. P-4788-I) | Trade Names: Stargon [®] , Stargon [®] SS (This product is intended for electric welding use.) |
| Chemical Name: Mixtures of argon, carbon dioxide, and oxygen or nitrogen | Synonyms: Not applicable. |
| Chemical Family: Not applicable. | Product Grades: None assigned. |
| Telephone: Emergencies: 1-800-645-4633* CHEMTREC: 1-800-424-9300* Routine: 1-800-PRAXAIR | Company Name: Praxair, Inc. 39 Old Ridgebury Road Danbury, CT 06810-5113 |

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).*

2. Hazards Identification

EMERGENCY OVERVIEW

**CAUTION! High-pressure gas.
Can cause rapid suffocation.
Can increase respiration and heart rate.
May cause dizziness and drowsiness.
Self-contained breathing apparatus may be required by rescue workers.
This mixture is a colorless, odorless gas at normal temperature and pressure.**

OSHA REGULATORY STATUS: The components of this mixture are considered hazardous by the OSHA Hazard Communications Standard (29 CFR 1910.1200).

POTENTIAL HEALTH EFFECTS:

Effects of a Single (Acute) Overexposure

Inhalation. Asphyxiant. Effects are due to lack of oxygen. The carbon dioxide component is also physiologically active, affecting circulation and breathing. Moderate concentrations may cause headache, drowsiness, dizziness, stinging of the nose and throat, excitation, rapid breathing and heart rate, excess salivation, vomiting, and unconsciousness. Lack of oxygen can kill.

Skin Contact. No harm expected.

Swallowing. This product is a gas at normal temperature and pressure.

Eye Contact. No harm expected.

Effects of Repeated (Chronic) Overexposure. No harm expected.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

Other Effects of Overexposure. Possible damage to retinal ganglion cells and central nervous system.

Medical Conditions Aggravated by Overexposure. The toxicology and the physical and chemical properties of this product suggest that overexposure is unlikely to aggravate existing medical conditions.

CARCINOGENICITY: None of the components of this mixture is listed by NTP, OSHA, or IARC.

POTENTIAL ENVIRONMENTAL EFFECTS: None known. For further information, see section 12, Ecological Information.

3. Composition/Information on Ingredients

This section covers materials of manufacture only. See sections 8, 10, 11, and 16 for information on by-products generated during use in welding and cutting. See section 16 for important information about mixtures.

| COMPONENT | CAS NUMBER | CONCENTRATION |
|----------------|------------|---------------|
| Argon | 7440-37-1 | ≥90%* |
| Carbon Dioxide | 124-38-9 | <10%* |
| Oxygen | 7782-44-7 | 0, < 5%* |
| Nitrogen | 7727-37-9 | 0, < 5%* |

*The symbol > means "greater than"; the symbol <, "less than."

4. First Aid Measures

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

SKIN CONTACT: No harm expected.

SWALLOWING: This product is a gas at normal temperature and pressure.

EYE CONTACT: No harm expected.

NOTES TO PHYSICIAN: *There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.*

5. Fire Fighting Measures

FLAMMABLE PROPERTIES: This mixture cannot catch fire.

SUITABLE EXTINGUISHING MEDIA: Use media appropriate for surrounding fire.

PRODUCTS OF COMBUSTION: Not applicable. Decomposition due to welding and heating may produce toxic by-products. See section 10.

PROTECTION OF FIREFIGHTERS: CAUTION! High-pressure gas. Asphyxiant—lack of oxygen can kill. Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool; then move them away from fire area if without risk.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

Self-contained breathing apparatus may be required by rescue workers. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

Specific Physical and Chemical Hazards. Heat of fire can build pressure in cylinder and cause it to rupture. No part of cylinder should be subjected to a temperature higher than 125°F (52°C). Stargon cylinders are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.)

Protective Equipment and Precautions for Firefighters. Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CAUTION! High-pressure gas.

Personal Precautions. Asphyxiant. Lack of oxygen can kill. Evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Shut off flow if you can do so without risk. Ventilate area or move cylinder to a well-ventilated area. Test for sufficient oxygen, especially in confined spaces, before allowing reentry.

Environmental Precautions. Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING: *Can cause rapid suffocation due to oxygen deficiency.* Store and use with adequate ventilation. Close cylinder valve after each use; keep closed even when empty. *Arcs and sparks can ignite combustible materials.* Prevent fires. For more information on fire prevention in welding and cutting, see NFPA 51B: *Standard for Fire Prevention During Welding, Cutting, and Other Hotwork*, published by the National Fire Protection Association. *Do not strike an arc on the cylinder.* The defect produced by an arc burn could lead to cylinder rupture. *Protect cylinders from damage.* Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. *Open valve slowly.* If valve is hard to open, discontinue use and contact your supplier. *Never apply flame or localized heat directly to any part of the cylinder.* High temperatures may damage the cylinder and could cause the pressure relief device to fail prematurely, venting the cylinder contents. For other precautions in using Stargon, see section 16.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store and use with adequate ventilation. *Firmly secure cylinders upright to keep them from falling or being knocked over.* Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125°F (52°C). *Store full and empty cylinders separately.* Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

RECOMMENDED PUBLICATIONS: For further information on storage, handling, and use, see Praxair publication P-14-153, *Guidelines for Handling Gas Cylinders and Containers*. Obtain from your local supplier.

8. Exposure Controls/Personal Protection

See section 16 for important information on by-products generated during use in welding and cutting.

| COMPONENT | OSHA PEL | ACGIH TLV-TWA (2007) |
|----------------|------------------|---------------------------------------|
| Argon | Not established. | Simple asphyxiant |
| Carbon Dioxide | Not established. | 5,000 ppm; 30,000 ppm, 15 min STEL |
| Oxygen | Not established. | Not established. |
| Nitrogen | Not established. | Simple asphyxiant |

TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

IDLH = Not applicable.

ENGINEERING CONTROLS:

Local Exhaust. Use a local exhaust system, if necessary, to prevent oxygen deficiency and to keep hazardous fumes and gases below all applicable exposure limits in the worker's breathing zone.

Mechanical (General). General exhaust ventilation may be acceptable if it can maintain an adequate supply of air and keep hazardous fumes and gases below all applicable exposure limits in the worker's breathing zone.

Special. None

Other. None

PERSONAL PROTECTIVE EQUIPMENT:

Skin Protection. Wear work gloves and metatarsal shoes for cylinder handling. Welding gloves for welding. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. For welding, see section 16. Regardless of protective equipment, never touch live electrical parts.

Eye/Face Protection. Wear safety glasses when handling cylinders. For welding, see section 16.

Respiratory Protection. Use air-purifying or air-supplied respirators, as appropriate, where local or general exhaust ventilation is inadequate. Adequate ventilation must keep worker exposure below all applicable exposure limits for fumes, gases, and other by-products of welding with Stargon. See section 16 for details. An air-supplied respirator must be used in confined spaces. Respiratory protection must conform to OSHA 29 CFR 1910.134. Select per OSHA 29 CFR 1910.134 and ANSI Z88.2.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

9. Physical and Chemical Properties

| | |
|---|---|
| APPEARANCE: | Colorless gas |
| ODOR: | None |
| ODOR THRESHOLD: | Not applicable. |
| PHYSICAL STATE: | Gas at normal temperature and pressure |
| pH: | Not applicable. |
| MELTING POINT at 1 atm: | Not available. |
| BOILING POINT at 1 atm: | Not available. |
| FLASH POINT (test method): | Not applicable. |
| EVAPORATION RATE (Butyl Acetate = 1): | Gas |
| FLAMMABILITY: | Nonflammable |
| FLAMMABLE LIMITS IN AIR , % by volume: | LOWER: Not applicable. UPPER: Not applicable. |
| VAPOR PRESSURE [DBW1]: | Not applicable. |
| GAS DENSITY at 70°F (21.1°C) and 1 atm: | 0.149 lb/ft ³ (1.68 kg/m ³) |
| SPECIFIC GRAVITY (Air = 1) at 70°F (21.1°C) and 1 atm: | Stargon: 1.4, Stargon SS: 1.376 |
| SOLUBILITY IN WATER 68°F (20°C): | Negligible |
| PARTITION COEFFICIENT: n-octanol/water: | Not available. |
| AUTOIGNITION TEMPERATURE: | Not applicable. |
| DECOMPOSITION TEMPERATURE: | None |
| PERCENT VOLATILES BY VOLUME: | 100 |
| MOLECULAR WEIGHT: | Not applicable. |
| MOLECULAR FORMULA: | Mixture of Ar, CO ₂ , and O ₂ or N ₂ |

10. Stability and Reactivity

CHEMICAL STABILITY: Unstable Stable

CONDITIONS TO AVOID: Contact with incompatible materials, exposure to electrical discharges, and/or high temperatures as stated below.

INCOMPATIBLE MATERIALS: Alkali metals, alkaline earth metals, metal acetylides, chromium, titanium above 1022°F (550°C), uranium above 1382°F (750°C), magnesium above 1427°F (775°C).

HAZARDOUS DECOMPOSITION PRODUCTS: The arc may form gaseous reaction products such as carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. See section 16. Other decomposition products of normal operation originate from the volatilization, reaction, or oxidation of the material being worked.

POSSIBILITY OF HAZARDOUS REACTIONS: May Occur Will Not Occur

Decomposition into toxic, flammable, and/or oxidizing materials under above-stated conditions.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

11. Toxicological Information

ACUTE DOSE EFFECTS: Carbon dioxide LC_{Lo} = 90,000 ppm, 5 min., human

The welding process may generate hazardous fumes and gases. (See sections 10 and 16.)

Carbon dioxide is an asphyxiant. It initially stimulates respiration and then causes respiratory depression. High concentrations result in narcosis. Symptoms in humans are as follows:

| <u>EFFECT:</u> | <u>CONCENTRATION:</u> |
|---|-----------------------|
| Breathing rate increases slightly. | 1% |
| Breathing rate increases to 50% above normal level. Prolonged exposure can cause headache, tiredness. | 2% |
| Breathing increases to twice normal rate and becomes labored. Weak narcotic effect. Impaired hearing, headache, increased blood pressure and pulse rate. | 3% |
| Breathing increases to approximately four times normal rate, symptoms of intoxication become evident, and slight choking may be felt. | 4 - 5% |
| Characteristic sharp odor noticeable. Very labored breathing, headache, visual impairment, and ringing in the ears. Judgment may be impaired, followed within minutes by loss of consciousness. | 5 - 10% |

REPRODUCTIVE EFFECTS: A single study has shown an increase in heart defects in rats exposed to 6% carbon dioxide in air for 24 hours at different times during gestation. There is no evidence that carbon dioxide is teratogenic in humans.

12. Ecological Information

ECOTOXICITY: No known effects.

OTHER ADVERSE EFFECTS: None expected. This mixture does not contain any Class I or Class II ozone-depleting chemicals.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

14. Transport Information

DOT/IMO SHIPPING NAME: Compressed gases, n.o.s. (argon, carbon dioxide, oxygen) or
Compressed gases, n.o.s. (argon, carbon dioxide, nitrogen)

| HAZARD CLASS: | PACKING GROUP/Zone: | IDENTIFICATION NUMBER: | PRODUCT RQ: |
|--|---------------------|------------------------|-------------|
| 2.2 | NA/NA* | UN1956 | None |
| SHIPPING LABEL(s): NONFLAMMABLE GAS | | | |
| PLACARD (when required): NONFLAMMABLE GAS | | | |

*NA = Not applicable.

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

MARINE POLLUTANTS: No component of this mixture is listed as a marine pollutant by DOT.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

U.S. FEDERAL REGULATIONS:

EPA (ENVIRONMENTAL PROTECTION AGENCY)

CERCLA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):

Reportable Quantity (RQ): None

SARA: SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:

SECTIONS 302/304: Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):

TPQ: None

EHS RQ (40 CFR 355): None

SECTIONS 311/312: Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:

IMMEDIATE: Yes

PRESSURE: Yes

DELAYED: No

REACTIVITY: No

FIRE: No

SECTION 313: Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

No component of this mixture is subject to reporting under Section 313.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION: Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

No component of this mixture is listed as a regulated substance.

TSCA: TOXIC SUBSTANCES CONTROL ACT: The components of this mixture are listed on the TSCA inventory.

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:

29 CFR 1910.119: PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

No component of this mixture is listed in Appendix A as a highly hazardous chemical.

STATE REGULATIONS:

CALIFORNIA: No component of this mixture is listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).

WARNING: Combustion of this gas produces carbon monoxide—a chemical known to the State of California to cause birth defects or other reproductive harm. (*California Health and Safety Code §25249.5 et seq.*)

PENNSYLVANIA: The components of this mixture are subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

16. Other Information

Be sure to read and understand all labels and instructions supplied with all containers of this product.

ADDITIONAL SAFETY AND HEALTH HAZARDS: Using this product in welding and cutting may create additional hazards:

FUMES AND GASES can be dangerous to your health and may cause serious lung disease.

- **Keep your head out of fumes. Do not breathe fumes and gases. Use enough ventilation, local exhaust, or both to keep fumes and gases from your breathing zone and the general area. Short-term overexposure to fumes may cause dizziness, nausea, and dryness or irritation of the nose, throat, and eyes or may cause other similar discomfort.**

Fumes and gases cannot be classified simply. The amount and type depend on the metal being worked and the process, procedure, equipment, and supplies used. Possible dangerous materials may be found in fluxes, electrodes, and other materials. Get an MSDS for every material you use.

Contaminants in the air may add to the hazard of fumes and gases. One such contaminant, chlorinated hydrocarbon vapors from cleaning and degreasing activities, poses a special risk.

- **Do not use electric arcs in the presence of chlorinated hydrocarbon vapors—highly toxic phosgene may be produced.**

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

Metal coatings such as paint, plating, or galvanizing may generate harmful fumes when heated. Residues from cleaning materials may also be harmful.

- **Avoid arc operations on parts with phosphate residues (anti-rust, cleaning preparations)—highly toxic phosphine may be produced.**

To find the quantity and content of fumes and gases, you can take air samples. By analyzing these samples, you can find out what respiratory protection you need. One recommended sampling method is to take air from inside the worker's helmet or from the worker's breathing zone. See AWS F1.1, *Methods for Sampling and Analyzing Gases for Welding and Allied Processes*, available from the American Welding Society, 550 N.W. Le Jeune Rd., Miami, FL 33126.

Read and understand the manufacturer's instructions and the precautionary labels on the products used in welding and cutting. Ask your welding products supplier for a copy of Praxair's free safety booklet, P-52-529, *Precautions and Safe Practices for Electric Welding and Cutting*, and for other manufacturers' safety publications. For a detailed treatment, read ANSI Z49.1, *Safety in Welding, Cutting, and Allied Processes*, published by the American Welding Society, or see OSHA's Web site at <http://www.osha-slc.gov/SLTC/weldingcuttingbrazing/>.

NOTES TO PHYSICIAN:

Acute: *Gases, fumes, and dusts may cause irritation to the eyes, lungs, nose, and throat. Some toxic gases associated with welding and related processes may cause pulmonary edema, asphyxiation, and death. Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty breathing, frequent coughing, or chest pains.*

Chronic: *Protracted inhalation of air contaminants may lead to their accumulation in the lungs, a condition that may be seen as dense areas on chest x-rays. The severity of change is proportional to the length of exposure. The changes seen are not necessarily associated with symptoms or signs of reduced lung function or disease. In addition, the changes on x-rays may be caused by non-work-related factors such as smoking, etc.*

PROTECTIVE CLOTHING AND EQUIPMENT FOR WELDING OPERATIONS:

PROTECTIVE GLOVES: Wear welding gloves.

EYE PROTECTION: Wear a helmet or use a face shield with a filter lens. Select lens per ANSI Z49.1. Provide protective screens and flash goggles if needed to protect others; select per OSHA 29 CFR 1910.133.

OTHER PROTECTIVE EQUIPMENT: Wear hand, head, and body protection. (See ANSI Z49.1.) Worn as needed, these help prevent injury from radiation, sparks, and electrical shock. Minimum protection includes welder's gloves and a face shield. For added protection, consider arm protectors, aprons, hats, shoulder protection, and dark, substantial clothing.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE: **High-pressure gas.** Use piping and equipment adequately designed to withstand pressures to be encountered. Use a backflow prevention device in any piping. **Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in a safe and environmentally sound manner in compliance with all federal, state, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.** When using compressed gases in and around electric welding applications,

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

never ground the cylinders. Grounding exposes the cylinders to damage by the electric welding arc.

Mixtures. When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

HAZARD RATING SYSTEMS:

NFPA RATINGS:

HEALTH = 1
FLAMMABILITY = 0
INSTABILITY = 0
SPECIAL = None

HMIS RATINGS:

HEALTH = 1
FLAMMABILITY = 0
PHYSICAL HAZARD = 3

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: CGA-580 (CGA-680 for 4K cylinder)
PIN-INDEXED YOKE: Not applicable.
ULTRA-HIGH-INTEGRITY CONNECTION: Not applicable.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlet V-1 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information can be found in the following materials published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, <http://www.cganet.com/Publication.asp>.

AV-1 *Safe Handling and Storage of Compressed Gases*
AV-8 *Characteristics and Safe Handling of Cryogenic Liquid and Gaseous Oxygen*
G-6 *Carbon Dioxide*
P-1 *Safe Handling of Compressed Gases in Containers*
P-9 *Inert Gases—Argon, Nitrogen, and Helium*
SB-2 *Oxygen-Deficient Atmospheres*
V-1 *Compressed Gas Cylinder Valve Inlet and Outlet Connections*
V-7 *Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures*
— *Handbook of Compressed Gases, Fourth Edition*

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

Product: Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Oxygen) or
Compressed Gases, N.O.S.
(Argon, Carbon Dioxide, Nitrogen)

P-4788-I

Date: December 2007

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current MSDSs for these products, contact your Praxair sales representative or local distributor or supplier, or download from www.praxair.com. If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

Praxair, the *Flowing Airstream* design, and *Stargon* are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.



Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113